


## Project name Ravenscroft, Cheddar, Somerset

**Project summary** A 162m<sup>2</sup> single storey self build in Cheddar. This property has been designed with two bedrooms both with ensuite bathrooms, at each end of the home separated by a large glazed kitchen and living room.



## Project Description

Projected build start date	01 Jan 2019
Projected date of occupation	01 Jan 2020
Project stage	Occupied
Project location	Cheddar, Somerset, England
Energy target	PassivHaus
Build type	New build
Building sector	Private Residential
Property type	Detached
Existing external wall construction	Softwood frame
Existing external wall additional information	
Existing party wall construction	

Floor area	162 m <sup>2</sup>
Floor area calculation method	PHPP

## Project team

Organisation	Beattie Passive
Project lead	
Client	
Architect	
Mechanical & electrical consultant(s)	
Energy consultant(s)	
Structural engineer	
Quantity surveyor	
Other consultant	
Contractor	

## Design strategies

Planned occupancy
Space heating strategy
Water heating strategy
Fuel strategy
Renewable energy generation strategy
Passive solar strategy
Space cooling strategy
Daylighting strategy
Ventilation strategy
Airtightness strategy
Strategy for minimising thermal bridges
Modelling strategy
Insulation strategy
Other relevant retrofit strategies
Other information (constraints or opportunities influencing project design or outcomes)

## Energy use

Fuel use by type (kWh/yr)

Fuel	previous	forecast	measured
<b>Electric</b>			
<b>Gas</b>			
<b>Oil</b>			
<b>LPG</b>			
<b>Wood</b>			

Fuel	previous	forecast	measured

### Primary energy requirement & CO2 emissions

	previous	forecast	measured
<b>Annual CO2 emissions</b> (kg CO2/m <sup>2</sup> .yr)	-	-	-
<b>Primary energy requirement</b> (kWh/m <sup>2</sup> .yr)	-	-	-

### Renewable energy (kWh/yr)

Renewables technology	forecast	measured
-		
-		
<b>Energy consumed by generation</b>		

### Airtightness ( m<sup>3</sup>/m<sup>2</sup>.hr @ 50 Pascals )

	Date of test	Test result
Pre-development airtightness	-	-
Final airtightness	-	-

### Annual space heat demand ( kWh/m<sup>2</sup>.yr )

	Pre-development	forecast	measured
<b>Space heat demand</b>	-	-	-

Whole house energy calculation method

Other energy calculation method

Predicted annual heating load

-

Other energy target(s)

## Building services

Occupancy

Space heating

Hot water

Ventilation

Controls

Cooking

Lighting

Appliances

Renewables

Strategy for minimising thermal bridges

## Building construction

---

## Storeys

Volume

Thermal fabric area

Roof description

Roof U-value

Walls description

Walls U-value

Party walls description

Party walls U-value

Floor description

Floor U-value

Glazed doors description

Glazed doors U-value

Opaque doors description

Opaque doors U-value

Windows description

Windows U-value

Windows energy transmittance  
(G-value)

Windows light transmittance

Rooflights description

Rooflights light transmittance

Rooflights U-value

---

## Project images















